



DS-GB21GB/I

desmonscientific.com/





STANDARD CONTROLLER FEATURES

End user interface	Display LED
Resolution (°C)	0,1
Maximum Number of Probes	3
Internal Led light	yes
Acoustic alarm	yes
Hot gas advanced defrost	yes

ALARMS AND FAILURES (ACOUSTIC AND VISUAL)

HACCP function	yes
"Power failure" Alarm	yes
"High / low temperature" Alarm	yes
"Open door" Alarm	yes
"Sensor fault" Alarm	yes
Clogged condenser Alarm	yes
Alarm recording (data logger of events - alarms)	yes

CONNECTIONS

RS 485 interface (not available if temperature data logger with USB port is installed)	optional
--	----------

SAFETY

Dry Contact for alarms remoting	yes
Freezing and overheating safety device	yes

OPTIONALS

Rechargeable back-up batteries	optional
Temperature datalogger with USB port	optional

STRUCTURE

Exterior dimensions WxDxH (mm)	2160x800x2120
Capacity (L)	2100
Interior dimensions WxDxH (mm)	2040x665x1520
Insulation (mm)	60
Temperature range (°C)	-10°-25°
Max. ambient temperature (°C)	43
Type of cooling unit	Monoblock
Power supply (V)	220V/240V
Frequency (Hz)	50
Power consumption (W)	1860
Weight (KG)	350
Shipping weight (KG)	375
Shipping dimensions WxDxH (mm)	2200x860x2280
No. of compressors.	1
Doors	3 glass doors
Automatic (smart) defrost and evaporation	yes
Castors	optional
Chart recorder	optional
Shelves (pcs)	9
Lock	yes
Interior material	s/steel AISI304
Exterior material	white powder coated steel

Gas

R404a

Price: € 0,00